

Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 04-24-2023 Version: 1.0 Supersedes: 01-05-2022

SECTION 1: Identification

Product identifier

Product form : Substance : Argon Substance name Chemical name : Argon CAS No : 7440-37-1 Formula : Ar

Other means of identification : Shielding gas, Argon 40, ADDvance Argon 5.0

Product group : Core Products

Recommended use and restrictions on use

Recommended uses and restrictions : Industrial use

Supplier

www.lindecanada.ca

Linde Canada inc. 500 — 5015 Spectrum Way Mississauga - Canada L4W 0E4 T 1-905-803-1600 - F 1-905-803-1682

Emergency telephone number

: 1-800-363-0042 **Emergency number**

Call emergency number 24 hours a day only for spills, leaks, fire, exposure, or accidents

involving this product.

For routine information, contact your supplier or Linde sales representative.

SECTION 2: Hazard identification

Classification of the substance or mixture

GHS-CA classification

Gases under pressure: Compressed gas

Simple Asphyxiant

GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms



: WARNING Signal word

: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED Hazard statements

MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION

: Do not handle until all safety precautions have been read and understood Precautionary statements

Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure.

Close valve after each use and when empty.

Protect from sunlight when ambient temperature exceeds 52°C (125°F).

Other hazards

Other hazards which do not result in : Asphyxiant in high concentrations.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

EN (English - CA) SDS ID: E-4563 1/8



Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 04-24-2023 Version: 1.0 Supersedes: 01-05-2022

classification

Unknown acute toxicity (GHS CA)

Not applicable

SECTION 3: Composition/information on ingredients

Substances

Name	CAS No.	% (Vol.)	Common Name (synonyms)
Argon (Main constituent)	(CAS No) 7440-37-1	100	Argon, compressed

Mixtures

Not applicable

SECTION 4: First-aid measures

Description of first aid measures

First-aid measures after inhalation

: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a physician.

First-aid measures after skin contact

: Adverse effects not expected from this product.

First-aid measures after eye contact

Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical attention. Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.

First-aid measures after ingestion

: Ingestion is not considered a potential route of exposure.

Most important symptoms and effects (acute and delayed)

Symptoms/injuries : No additional information available

Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : None.

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media

No additional information available

Specific hazards arising from the hazardous product

Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

Reactivity in case of fire

: No reactivity hazard other than the effects described in sub-sections below.

Special protective equipment and precautions for fire-fighters

Firefighting instructions

Protection during firefighting

: Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with their provincial and local fire code regulations.

: Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen.

Special protective equipment for fire fighters

: Use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

SDS ID: E-4563 EN (English - CA) 2/8



Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 04-24-2023 Supersedes: 01-05-2022 Version: 1.0

Specific methods

: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

Stop flow of product if safe to do so.

Use water spray or fog to knock down fire fumes if possible.

Other information : Containers are equipped with a pressure relief device. (Exceptions may exist where

authorized.).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Evacuate area. Ensure adequate air ventilation. Wear self-contained breathing apparatus when entering area unless atmosphere is proven to be safe. Stop leak if safe to do so.

Personal Precautions, Protective Equipment and Emergency Procedures

General measures: Ensure adequate ventilation. Personal Precautions, Protective Equipment and Emergency Procedures: EVACUATE ALL PERSONNEL FROM AFFECTED AREA. Use appropriate protective equipment. If leak is on user's equipment, be certain to purge piping before attempting repairs. If leak is on a container or container valve contact the closest Linde Canada location.

6.2. Methods and materials for containment and cleaning up

For containment

: Try to stop release if safe to do so.

Methods for cleaning up

: This material and its container must be disposed of in a safe way, and as per local legislation. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g, wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 52 °C (125 °F). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

EN (English - CA) SDS ID : E-4563 3/8



Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 04-24-2023 Supersedes: 01-05-2022 Version: 1.0

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Consider work permit system e.g. for maintenance activities. Provide adequate general and local exhaust ventilation. Ensure exposure is below occupational exposure limits (where available).

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment

: Gloves. Face shield. Safety glasses.







Hand protection

: Wear work gloves when handling containers. Wear heavy rubber gloves where contact with

product may occur.

Eye protection

: Wear goggles and a face shield when transfilling or breaking transfer connections. Wear safety glasses with side shields. Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines. Safety eye wear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or

dusts. Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face

Protection", and any provincial regulations, local bylaws or guidelines.

Respiratory protection

Respiratory protection: Use air supplied respirator when working in confined space or where local exhaust or ventilation does not keep exposure below OEL (if applicable). Select in accordance with provincial regulations, local bylaws or guidelines. Respirators should also be approved by NIOSH and MSHA. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCRA)

use a self-contained breathing apparatus (SCBA).

Thermal hazard protection

: Wear cold insulating gloves when transfilling or breaking transfer connections. None necessary.

Environmental exposure controls

None necessary.

Other information

Other protection: Safety shoes for general handling at customer sites. Metatarsal shoes and cuffless trousers for cylinder handling at packaging and filling plants. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines. For working with flammable and oxidizing materials, consider the use of flame resistant anti-static safety clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(a) Physical state : Gas
(b) Colour : Colourless.

(c) Odour : No odour warning properties.

Odour threshold : No data available

(d) Melting point : -189 °C

Freezing point : No data available

(e) Boiling point : $-185.9 \,^{\circ}\text{C}$ (f) Flammability : Non flammable

(g) Flammability (solid, gas)

(h) Flash point : No data available
(i) Auto-ignition temperature : Not applicable.
(j) Decomposition temperature : No data available
(k) pH : Not applicable.
(l) Viscosity, kinematic : Not applicable.
(m) Solubility : Water: 61 mg/l
(n) Partition coefficient – n-octanol/water [log Pow/log Kow]

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download.

Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

EN (English - CA) SDS ID : E-4563 4/8



Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 04-24-2023 Supersedes: 01-05-2022 Version: 1.0

(o) Vapour pressure : Not applicable.

(p) Density : Vapour density 0.103 lb/ft³ at 21.1°C (70°F)

Relative gas density : 1.38

(r) Particle characteristics : No data available

(s) Molecular mass : 40 g/mol
(t) Critical temperature : -122.4 °C
(u) Critical pressure : 4898 kPa
(v) Oxidizing properties : None.

(w) Relative evaporation rate (butylacetate=1)Relative evaporation rate (ether=1)Not applicable.

9.2. Other information

Gas group : Compressed gas

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

SECTION 10: Stability and reactivity

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : None. Conditions to avoid : None.

Incompatible materials : Using this product in welding and cutting may create additional hazards. The arc from electric

arc welding may form gaseous reaction products such as carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. Other decomposition products of arc welding and cutting originate from the volatilization, reaction, and oxidization of

the material being worked.

Hazardous decomposition products : None.

SECTION 11: Toxicological information

11.1 Likely routes of exposure : Inhalation.

11.2 Symptoms related to the physical, chemical, and toxicological characteristics

: No additional information available

11.3 Delayed and immediate effects and chronic effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified
Skin corrosion/irritation : Not classified

pH: Not applicable.

Serious eye damage/irritation : Not classified

pH: Not applicable.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download.

Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

EN (English - CA) SDS ID : E-4563 5/8



Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 04-24-2023 Supersedes: 01-05-2022 Version: 1.0

Specific target organ toxicity (single exposure)

Specific target organ toxicity (repeated

exposure)

: Not classified: Not classified

Aspiration hazard

: Not classified

11.4 Toxicity

Argon (\f)7440-37-1	
LC50 inhalation rat (ppm)	No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecological damage caused by this product.

12.2. Persistence and degradability

Argon (7440-37-1)	
Persistence and degradability	No ecological damage caused by this product.

12.3. Bioaccumulative potential

Argon (7440-37-1)		
Log Pow	Not applicable.	
Log Kow	Not applicable.	
Bioaccumulative potential	No ecological damage caused by this product.	

12.4. Mobility in soil

Argon (7440-37-1)		
Mobility in soil	No data available.	
Log Pow	Not applicable.	
Log Kow	Not applicable.	
Ecology - soil	No ecological damage caused by this product.	

12.5. Other adverse effects

Effect on the ozone layer : None.
Effect on global warming : None.

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations

Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

TDG

UN-No. (TDG) : UN1006

TDG Primary Hazard Classes : 2.2 - Class 2.2 - Non-Flammable, Non-Toxic Gases

Proper shipping name : ARGON, COMPRESSED

Explosive Limit and Limited Quantity Index : 0.125 L

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download.

Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

EN (English - CA) SDS ID : E-4563 6/8



Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 04-24-2023 Supersedes: 01-05-2022 Version: 1.0

Passenger Carrying Road Vehicle or Passenger : 75 L

Carrying Railway Vehicle Index

14.2. Air and sea transport

IMDG

UN-No. (IMDG) : 1006

Proper Shipping Name (IMDG) : ARGON, COMPRESSED

Class (IMDG) : 2 - Gases MFAG-No : 121

IATA

UN-No. (IATA) : 1006

Proper Shipping Name (IATA) : Argon, compressed

Class (IATA) : 2 - Gases

SECTION 15: Regulatory information

15.1. National regulations

Argon (7440-37-1)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Argon (7440-37-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

 Date of issue
 : 15/10/1979

 Revision date
 : 24/04/2023

 Supersedes
 : 05/01/2022

Indication of changes:

Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Other information : When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture.

Consult an industrial hygienist or other trained person when you evaluate the end product.

Before using any plastics, confirm their compatibility with this product.

Linde Canada asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Linde Canada Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Canada Inc, it is the user's obligation to determine the conditions of safe use of the product. Linde Canada Inc, SDSs are furnished on sale or delivery by Linde Canada Inc, or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Linde sales representative, local distributor, or supplier, or download from www.lindecanada.ca.

EN (English - CA) SDS ID : E-4563 7/8



Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 04-24-2023 Supersedes: 01-05-2022 Version: 1.0

NFPA health hazard

NFPA specific hazard

NFPA fire hazard

NFPA instability


: 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.

: 0 - Materials that will not burn.

: 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

: SA - This denotes gases which are simple asphyxiants.



HMIS III Rating

Health : 0 Minimal Hazard - No significant risk to health

: 0 Minimal Hazard - Materials that will not burn

Flammability
Physical

: 3 Serious Hazard - Materials that may form explosive mixtures with water and are capable of detonation or explosive reaction in the presence of a strong initiating source. Materials may polymerize, decompose, self-react, or undergo other chemical change at normal temperature and pressure with moderate risk of explosion

SDS Canada (GHS) - Linde NEW

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

EN (English - CA) SDS ID : E-4563 8/8