

Safety Data Sheet E-4638

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 07-28-2023 Version: 1.1 Supersedes: 01-01-2021

SECTION 1: Identification

Product identifier

Product form : Substance : Oxygen Substance name CAS No : 7782-44-7 : 02

Formula

Oxygen, Compressed; MediPure Oxygen; Aviator's Breathing Oxygen; USP Oxygen; Other means of identification

Oxygen - Diving Grade; Dioxygen

Product group : Core Products

Recommended use and restrictions on use

Recommended uses and restrictions : Medical applications, Industrial use, Diving Gas (Underwater Breathing)

Supplier

Linde Canada inc. 500 - 5015 Spectrum Way Mississauga - Canada L4W 0E4 T 1-905-803-1600 - F 1-905-803-1682 www.lindecanada.ca

Emergency telephone number

Emergency number : 1-800-363-0042

Call emergency number 24 hours a day only for spills, leaks, fire, exposure, or accidents

involving this product.

For routine information, contact your supplier or Linde sales representative.

SECTION 2: Hazard identification

Classification of the substance or mixture

GHS-CA classification

Oxidising Gases, Category 1 H270 Gases under pressure: Compressed gas H280

GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms





GHS04

Signal word : DANGER

Hazard statements : MAY CAUSE OR INTENSIFY FIRE; OXIDIZER

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

Do not handle until all safety precautions have been read and understood Precautionary statements

Keep away from clothing and other combustible materials

Keep valves and fittings free from oil and grease IN CASE OF FIRE: Stop leak if safe to do so

Use and store only outdoors or in a well-ventilated area.

Protect from sunlight when ambient temperature exceeds 52°C (125°F).

Use a back flow preventive device in the piping.

Use only with equipment of compatible materials of construction and rated for cylinder

pressure.

DO NOT change or force fit connections.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

EN (English - CA) SDS ID: E-4638 1/9



Safety Data Sheet E-4638

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 07-28-2023 Supersedes: 01-01-2021 Version: 1.1

Avoid spills. Do not walk on or roll equipment over spills. Use only with equipment cleaned for oxygen service.

Open valve slowly.

Close valve after each use and when empty.

2.3. Other hazards

Other hazards which do not result in classification

: Breathing 80 percent or more oxygen at atmospheric pressure for more than a few hours may cause nasal stuffiness, cough, sore throat, chest pain, and breathing difficulty. Breathing oxygen at higher pressure increases the likelihood of adverse effects within a shorter time period. Breathing pure oxygen under pressure may cause lung damage and central nervous system (CNS) effects, resulting in dizziness, poor coordination, tingling sensation, visual and hearing disturbances, muscular twitching, unconsciousness, and convulsions. Breathing oxygen under pressure may cause prolongation of adaptation to darkness and reduced peripheral vision.

2.4. Unknown acute toxicity (GHS CA)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

 Name
 : Oxygen

 CAS No
 : 7782-44-7

 EC no
 : 231-956-9

 EC index no
 : 008-001-00-8

Name	CAS No.	% (Vol.)	Common Name (synonyms)
Oxygen	(CAS No) 7782-44-7	99.5 – 100	Oxygen (dissolved) / Oxygen gas / Oxygen, compressed / Oxygen, dissolved

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Get medical advice/attention. Remove to fresh air and keep at rest in a position comfortable for

breathing.

First-aid measures after skin contact : Adverse effects not expected from this product.

First-aid measures after eye contact : In case of eye irritation: Rinse immediately with plenty of water. Consult an ophthalmologist if

irritation persists.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/injuries : No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : None.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Vigorously accelerates combustion. Use media appropriate for surrounding fire. Water (e.g,

safety shower) is the preferred extinguishing media for clothing fires.

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Fire hazard : Oxidizing agent; vigorously accelerates combustion. Contact with flammable materials may

cause fire or explosion.

Explosion hazard : CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Reactivity : No additional information available.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download.

Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

EN (English - CA) SDS ID : E-4638 2/9



Safety Data Sheet E-4638

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 07-28-2023 Version: 1.1 Supersedes: 01-01-2021

Reactivity in case of fire

: No reactivity hazard other than the effects described in sub-sections below.

Special protective equipment and precautions for fire-fighters

Firefighting instructions

: High-pressure, oxidizing gas.

Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must

comply with their provincial and local fire code regulations.

Protection during firefighting

Special protective equipment for fire fighters

Self-contained breathing apparatus.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Specific methods

Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

Stop flow of product if safe to do so.

Use water spray or fog to knock down fire fumes if possible.

Other information

Heat of fire can build pressure in container and cause it to rupture. Cylinders are equipped with a pressure relief device. (Exceptions may exist where authorized by TC.) No part of the container should be subjected to a temperature higher than 125°F (52°C). Smoking, flames, and electric sparks in the presence of enriched oxygen atmospheres are potential explosion hazards.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures

: Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ensure adequate air ventilation. Eliminate ignition sources. Evacuate area. Try to stop release. Monitor concentration of released product. Wear self-contained breathing apparatus when entering area unless atmosphere is proven to be safe. Stop leak if safe to do

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Not applicable.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

Safe use of the product

The suitability of this product as a component in underwater breathing gas mixtures is to be determined by or under the supervision of personnel experienced in the use of underwater breathing gas mixtures and familiar with the physiological effects, methods employed, frequency and duration of use, hazards, side effects, and precautions to be taken.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

SDS ID: E-4638 EN (English - CA) 3/9



Safety Data Sheet E-4638

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 07-28-2023 Supersedes: 01-01-2021 Version: 1.1

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store only where temperature will not exceed 52 °C (125 °F). Post "No Smoking/No Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g.: CSA, TSSA, or NFPA Codes), or according to the provincial requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Avoid oxygen rich (>23,5%) atmospheres. Use a local exhaust system with sufficient flow velocity to maintain an adequate supply of air in the worker's breathing zone. Mechanical (general): General exhaust ventilation may be acceptable if it can maintain an adequate supply of air.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment

: Safety glasses. Face shield. Gloves







Hand protection

: Wear work gloves when handling containers. Wear heavy rubber gloves where contact with product may occur.

Eye protection

: Wear goggles when transfilling or breaking transfer connections. Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

Respiratory protection

: Respiratory protection: Use air supplied respirator when working in confined space or where local exhaust or ventilation does not keep exposure below OEL (if applicable). Select in accordance with provincial regulations, local bylaws or guidelines. Respirators should also be approved by NIOSH and MSHA. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

Environmental exposure controls

: **Environmental exposure controls:** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Other information

: Other protection: Safety shoes for general handling at customer sites. Metatarsal shoes and cuffless trousers for cylinder handling at packaging and filling plants. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines. For working with flammable and oxidizing materials, consider the use of flame resistant anti-static safety clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(a) Physical state : Gas
(b) Colour : Colourless.

(c) Odour : No odour warning properties.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download.

Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

EN (English - CA) SDS ID : E-4638 4/9



Safety Data Sheet E-4638

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 07-28-2023 Supersedes: 01-01-2021 Version: 1.1

Odour threshold : No data available (d) Melting point : ≥ -219 °C (-362°F) Freezing point : ≥ -219 (-362°F) -183 °C (-297°F) (e) Boiling point (f) Flammability : Non flammable (g) Flammability (solid, gas) : Non flammable : Not applicable. (h) Flash point (i) Auto-ignition temperature : Non flammable. (j) Decomposition temperature : No data available Hq (k) : Not applicable. (I) Viscosity, kinematic : Not applicable. (m) Solubility : Water: 39 mg/l : Not applicable.

(n) Partition coefficient - n-octanol/water [log

Pow/log Kow]

(o) Vapour pressure : Not applicable.

: 1.4289 kg/m³ (at 21.1 °C) (p) Density

Relative gas density

(r) Particle characteristics : No data available

(s) Molecular mass : 32 g/mol

: -118.6 °C (-181.48°F) (t) Critical temperature (u) Critical pressure : 50.4 bar (731.4 psia)

(v) Oxidizing properties : Oxidizer.

(w) Relative evaporation rate (butylacetate=1) : No data available Relative evaporation rate (ether=1) : Not applicable.

92 Other information

Gas group : Compressed gas

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

SECTION 10: Stability and reactivity

: No additional information available. Reactivity Chemical stability Stable under normal conditions. Possibility of hazardous reactions Violently oxidizes organic material.

Conditions to avoid : None.

: Keep equipment free from oil and grease. Consider the potential toxicity hazard due to the Incompatible materials

presence of chlorinated or fluorinated polymers in high pressure (> 30 bar) oxygen lines in case of combustion. May react violently with combustible materials. May react violently with reducing

agents.

Hazardous decomposition products : None.

SECTION 11: Toxicological information

11.1 Likely routes of exposure : Inhalation

11.2 Symptoms related to the physical, chemical, and toxicological characteristics : No additional information available

11.3 Delayed and immediate effects and

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

SDS ID: E-4638 EN (English - CA) 5/9



Safety Data Sheet E-4638

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 07-28-2023 Supersedes: 01-01-2021 Version: 1.1

chronic effects

: Not classified Acute toxicity (oral) Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified Skin corrosion/irritation : Not classified

pH: Not applicable.

Serious eye damage/irritation : Not classified

pH: Not applicable.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard

: Not classified

11.4 Toxicity

Oxygen (\f)7782-44-7	
LC50 inhalation rat (ppm)	No data available

SECTION 12: Ecological information

Toxicity

Oxygen (7782-44-7)

Oxygen (7782-44-7)

Ecology - general : No ecological damage caused by this product.

12.2. Persistence and degradability

- , ,	7 5 (· · · /		
Persist	ence and degradability	No ecological damage caused by this product.	
Oxyge	ygen (7782-44-7)		
Persistence and degradability		No data available.	
12.3.	Bioaccumulative potential		

Log Pow	Not applicable.
Log Kow	Not applicable.

Bioaccumulative potential	potential No ecological damage caused by this product.	
Oxygen (7782-44-7)		
Log Pow	Not applicable.	

Log Kow Not applicable. Bioaccumulative potential No ecological damage caused by this product.

12.4. **Mobility in soil**

Oxygen (7782-44-7)	
Mobility in soil	No data available.
Log Pow	Not applicable.
Log Kow	Not applicable.
Ecology - soil	No ecological damage caused by this product.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

SDS ID: E-4638 EN (English - CA) 6/9



Safety Data Sheet E-4638

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 07-28-2023 Supersedes: 01-01-2021 Version: 1.1

xygen (7782-44-7)	
Mobility in soil	No data available.
Log Pow	Not applicable.
Log Kow	Not applicable.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.

12.5. Other adverse effects

Effect on the ozone layer : None.

Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international

regulations. Contact supplier for any special requirements.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

TDG

UN-No. (TDG) : UN1072

TDG Primary Hazard Classes : 2.2 - Class 2.2 - Non-Flammable, Non-Toxic Gases

TDG Subsidiary Classes : 5.1

Proper shipping name : OXYGEN, COMPRESSED

ERAP Index : 3 000

Explosive Limit and Limited Quantity Index : 0.125 L (0,125 L)

Passenger Carrying Road Vehicle or Passenger : 75 L

Carrying Railway Vehicle Index

14.2. Air and sea transport

IMDG

UN-No. (IMDG) : 1072

Proper Shipping Name (IMDG) : OXYGEN, COMPRESSED

Class (IMDG) : 2 - Gases MFAG-No : 122

IATA

UN-No. (IATA) : 1072

Proper Shipping Name (IATA) : Oxygen, compressed

Class (IATA) : 2 - Gases

SECTION 15: Regulatory information

15.1. National regulations

Oxygen (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

Oxygen (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download.

Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.

EN (English - CA) SDS ID : E-4638 7/9



Safety Data Sheet E-4638

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 07-28-2023 Version: 1.1 Supersedes: 01-01-2021

15.2. International regulations

Oxygen (7782-44-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Oxygen (7782-44-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

: 15/10/1979 Date of issue Revision date : 28/07/2023 Supersedes : 01/01/2021

Indication of changes:

Training advice : Ensure operators understand the hazard of oxygen enrichment.

Linde Canada asks users of this product to study this SDS and become aware of the product Other information hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product

hazards and safety information.

The opinions expressed herein are those of qualified experts within Linde Canada Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Canada Inc, it is the user's obligation to determine the conditions of safe use of the product. Linde Canada Inc, SDSs are furnished on sale or delivery by Linde Canada Inc, or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Linde sales representative, local distributor, or supplier, or download from www.lindecanada.ca.

NFPA health hazard : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.


NFPA fire hazard : 0 - Materials that will not burn.

NFPA instability : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

NFPA specific hazard OX - This denotes an oxidizer, a chemical which can

greatly increase the rate of combustion/fire.



HMIS III Rating

: 0 Minimal Hazard - No significant risk to health Health Flammability : 0 Minimal Hazard - Materials that will not burn

: 3 Serious Hazard - Materials that may form explosive mixtures with water and are capable of **Physical** detonation or explosive reaction in the presence of a strong initiating source. Materials may polymerize, decompose, self-react, or undergo other chemical change at normal temperature

and pressure with moderate risk of explosion

SDS ID: E-4638 EN (English - CA) 8/9



Oxygen Safety Data Sheet E-463

Safety Data Sheet E-4638 according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 07-28-2023 Supersedes: 01-01-2021 Version: 1.1

SDS Canada (GHS) - Linde NEW

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

EN (English - CA) SDS ID : E-4638 9/9