



# NI - Pentane Mixture

## Safety Data Sheet E-7096

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06-01-2017

Revision date: 07-28-2023

Supersedes: 01-01-2021

Version: 1.1

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
Product name : NI - Pentane Mixture  
Other means of identification : NI - Pentane 1.8 - 11%  
Product group : Core Products

#### 1.2. Recommended use and restrictions on use

Recommended uses and restrictions : Industrial use

#### 1.3. Supplier

Linde Canada inc.  
500 — 5015 Spectrum Way  
Mississauga - Canada L4W 0E4  
T 1-905-803-1600 - F 1-905-803-1682  
[www.lindecana.ca](http://www.lindecana.ca)

#### 1.4. Emergency telephone number

Emergency number : 1-800-363-0042  
Call emergency number 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product.  
For routine information, contact your supplier or Linde sales representative.

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS-CA classification

Flammable gases, Category 1 H220  
Gases under pressure : Liquefied gas H280

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-CA labelling

Hazard pictograms :    
GHS02 GHS04

Signal word : DANGER

Hazard statements : **EXTREMELY FLAMMABLE GAS**  
CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

Precautionary statements : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Use and store only outdoors or in a well-ventilated area.  
LEAKING GAS FIRE: Do not extinguish, unless leak can be stopped safely.  
In case of leakage, eliminate all ignition sources  
Protect from sunlight when ambient temperature exceeds 52°C (125°F).  
Use a back flow preventive device in the piping.  
Close valve after each use and when empty.  
Do not open valve until connected to equipment prepared for use.

#### 2.3. Other hazards

Other hazards which do not result in classification : Asphyxiant in high concentrations.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download.  
Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.



# NI - Pentane Mixture

## Safety Data Sheet E-7096

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06-01-2017

Revision date: 07-28-2023

Supersedes: 01-01-2021

Version: 1.1

### 2.4. Unknown acute toxicity (GHS CA)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	CAS No.	% (Vol)	Common Name (synonyms)
Nitrogen	(CAS No) 7727-37-9	87 – 99.2	Nitrogen (liquified) / Nitrogen gas / Nitrogen, liquefied / NITROGEN / Nitrogen, compressed
n-Pentane	(CAS No) 109-66-0	1.8 – 11	Pentane / Normal pentane / PENTANE / Pentane, n- / Pentane(n-)

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a physician.
First-aid measures after skin contact	: The liquid may cause frostbite. For exposure to liquid, immediately warm frostbite area with warm water not to exceed 105°F (41°C). Water temperature should be tolerable to normal skin. Maintain skin warming for at least 15 minutes or until normal coloring and sensation have returned to the affected area. In case of massive exposure, remove clothing while showering with warm water. Seek medical evaluation and treatment as soon as possible.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.
First-aid measures after ingestion	: Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/injuries	: No additional information available
-------------------	---------------------------------------

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: None.
-----------------------------------	---------

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media	: Carbon dioxide, Dry chemical, Water spray or fog. Use extinguishing media appropriate for surrounding fire.
------------------------------	---

### 5.2. Unsuitable extinguishing media

No additional information available

### 5.3. Specific hazards arising from the hazardous product

Fire hazard	: <b>EXTREMELY FLAMMABLE GAS.</b>
Explosion hazard	: <b>EXTREMELY FLAMMABLE GAS.</b> Forms explosive mixtures with air and oxidizing agents.
Reactivity	: No reactivity hazard other than the effects described in sub-sections below.
Reactivity in case of fire	: No reactivity hazard other than the effects described in sub-sections below.

### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with their provincial and local fire code regulations.
Protection during firefighting	: Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen. <b>DANGER! FLAMMABLE, HIGH PRESSURE GAS..</b>
Special protective equipment for fire fighters	: Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.



# NI - Pentane Mixture

## Safety Data Sheet E-7096

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06-01-2017

Revision date: 07-28-2023

Supersedes: 01-01-2021

Version: 1.1

Other information : Containers are equipped with a pressure relief device. (Exceptions may exist where authorized.).

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : If venting or leaking gas catches fire, do not extinguish flames. Flammable vapors may spread from leak, creating an explosive reignition hazard. Vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering an area, especially a confined area, check the atmosphere with an appropriate device.

#### 6.2. Methods and materials for containment and cleaning up

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Use only explosion-proof equipment.

Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g. wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store only where temperature will not exceed 52 °C (125 °F). Post "No Smoking/No Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g.: CSA, TSSA, or NFPA Codes), or according to the provincial requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 52 °C (125 °F). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

**OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE:** When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

n-Pentane (109-66-0)		
USA - ACGIH	ACGIH OEL TWA [ppm]	1000 ppm

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.



# NI - Pentane Mixture

## Safety Data Sheet E-7096

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06-01-2017

Revision date: 07-28-2023

Supersedes: 01-01-2021

Version: 1.1

n-Pentane (109-66-0)		
USA - OSHA	OSHA PEL TWA [1]	2950 mg/m <sup>3</sup>
USA - OSHA	OSHA PEL TWA [2]	1000 ppm
Canada (Quebec)	VEMP (OEL TWA)	350 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (OEL TWA) [ppm]	120 ppm
Alberta	OEL TWA	1770 mg/m <sup>3</sup>
Alberta	OEL TWA [ppm]	600 ppm
British Columbia	OEL TWA [ppm]	1000 ppm
Manitoba	OEL TWA [ppm]	1000 ppm
New Brunswick	OEL STEL	2210 mg/m <sup>3</sup>
New Brunswick	OEL STEL [ppm]	750 ppm
New Brunswick	OEL TWA	1770 mg/m <sup>3</sup>
New Brunswick	OEL TWA [ppm]	600 ppm
New Foundland & Labrador	OEL TWA [ppm]	1000 ppm
Nova Scotia	OEL TWA [ppm]	1000 ppm
Nunavut	OEL STEL	2213 mg/m <sup>3</sup>
Nunavut	OEL STEL [ppm]	750 ppm
Nunavut	OEL TWA	1771 mg/m <sup>3</sup>
Nunavut	OEL TWA [ppm]	600 ppm
Northwest Territories	OEL STEL [ppm]	750 ppm
Northwest Territories	OEL TWA [ppm]	600 ppm
Ontario	OEL TWA [ppm]	1000 ppm
Prince Edward Island	OEL TWA [ppm]	1000 ppm
Québec	VEMP (OEL TWA)	350 mg/m <sup>3</sup>
Québec	VEMP (OEL TWA) [ppm]	120 ppm
Saskatchewan	OEL STEL [ppm]	750 ppm
Saskatchewan	OEL TWA [ppm]	600 ppm
Yukon	OEL STEL	2250 mg/m <sup>3</sup>
Yukon	OEL STEL [ppm]	750 ppm
Yukon	OEL TWA	1800 mg/m <sup>3</sup>
Yukon	OEL TWA [ppm]	600 ppm

### 8.2. Appropriate engineering controls

Appropriate engineering controls

: Use an explosion-proof local exhaust system. Local exhaust and general ventilation must be adequate to meet exposure standards. MECHANICAL (GENERAL): **Inadequate - Use only in a closed system.** Use explosion proof equipment and lighting. Provide adequate general and local exhaust ventilation. Ensure exposure is below occupational exposure limits (where available).

### 8.3. Individual protection measures/Personal protective equipment

Personal protective equipment

: Gloves. Face shield. Safety glasses.



Hand protection

: Wear work gloves when handling containers. Wear heavy rubber gloves where contact with product may occur.

Eye protection

: Wear safety glasses with side shields. Safety eye wear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.



# NI - Pentane Mixture

## Safety Data Sheet E-7096

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06-01-2017

Revision date: 07-28-2023

Supersedes: 01-01-2021

Version: 1.1

Respiratory protection	: <b>Respiratory protection:</b> Use air supplied respirator when working in confined space or where local exhaust or ventilation does not keep exposure below OEL (if applicable). Select in accordance with provincial regulations, local bylaws or guidelines. Respirators should also be approved by NIOSH and MSHA. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).
Thermal hazard protection	: Wear cold insulating gloves when transfilling or breaking transfer connections.
Other information	: <b>Other protection :</b> Safety shoes for general handling at customer sites. Metatarsal shoes and cuffless trousers for cylinder handling at packaging and filling plants. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines. For working with flammable and oxidizing materials, consider the use of flame resistant anti-static safety clothing.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

(a) Physical state	: Liquid
(b) Colour	: Colourless.
(c) Odour	: No data available.
Odour threshold	: No data available
(d) Melting point	: No data available
Freezing point	: No data available
(e) Boiling point	: No data available
(f) Flammability	: Flammable
(g) Flammability (solid, gas)	:
(h) Flash point	: No data available
(i) Auto-ignition temperature	: No data available
(j) Decomposition temperature	: No data available
(k) pH	: Not applicable.
(l) Viscosity, kinematic	: Not applicable.
(m) Solubility	: Water: No data available
(n) Partition coefficient – n-octanol/water [log Pow/log Kow]	: Not applicable.
(o) Vapour pressure	: Not applicable.
(p) Density	:
Relative gas density	: No data available
(r) Particle characteristics	: No data available
(v) Oxidizing properties	: None.
(w) Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable.

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

Reactivity	: No reactivity hazard other than the effects described in sub-sections below.
Chemical stability	: Stable under normal conditions.
Conditions to avoid	: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

## SECTION 11: Toxicological information

<b>11.1 Likely routes of exposure</b>	: Inhalation
---------------------------------------	--------------

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.



# NI - Pentane Mixture

## Safety Data Sheet E-7096

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06-01-2017

Revision date: 07-28-2023

Supersedes: 01-01-2021

Version: 1.1

### 11.2 Symptoms related to the physical, chemical, and toxicological characteristics

: No additional information available

### 11.3 Delayed and immediate effects and chronic effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified pH: Not applicable.
Serious eye damage/irritation	: Not classified pH: Not applicable.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

### 11.4 Toxicity

NI - Pentane Mixture	
LC50 inhalation rat (ppm)	No data available

n-Pentane (109-66-0)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	364 g/m <sup>3</sup> (Exposure time: 4 h)
LC50 inhalation rat (ppm)	246702 ppm/1h

## SECTION 12: Ecological information

### 12.1. Toxicity

n-Pentane (109-66-0)	
LC50 - Fish [1]	9.87 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
LC50 - Fish [2]	11.59 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 - Crustacea [1]	9.74 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### 12.2. Persistence and degradability

NI - Pentane Mixture	
Persistence and degradability	No ecological damage caused by this product.

Nitrogen (7727-37-9)	
Persistence and degradability	No ecological damage caused by this product.

n-Pentane (109-66-0)	
Persistence and degradability	May cause long-term adverse effects in the environment.

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.



# NI - Pentane Mixture

## Safety Data Sheet E-7096

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06-01-2017

Revision date: 07-28-2023

Supersedes: 01-01-2021

Version: 1.1

### 12.3. Bioaccumulative potential

NI - Pentane Mixture	
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.
Nitrogen (7727-37-9)	
Log Pow	Not applicable for inorganic gases.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.
n-Pentane (109-66-0)	
Log Pow	3.39

### 12.4. Mobility in soil

NI - Pentane Mixture	
Mobility in soil	No data available.
Log Pow	Not applicable.
Log Kow	Not applicable.
Nitrogen (7727-37-9)	
Mobility in soil	No data available.
Log Pow	Not applicable for inorganic gases.
Log Kow	Not applicable.
Ecology - soil	No ecological damage caused by this product.
n-Pentane (109-66-0)	
Log Pow	3.39

### 12.5. Other adverse effects

Effect on the ozone layer : None.

## SECTION 13: Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

## SECTION 14: Transport information

### 14.1. Basic shipping description

In accordance with TDG

#### TDG

UN-No. (TDG) : UN3161  
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gases  
Proper shipping name : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
  
ERAP Index : 3 000  
Explosive Limit and Limited Quantity Index : 0.125 L

### 14.2. Air and sea transport

#### IMDG

UN-No. (IMDG) : 3161  
Proper Shipping Name (IMDG) : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
Class (IMDG) : 2.1 - Flammable gases

#### IATA

UN-No. (IATA) : 3161  
Proper Shipping Name (IATA) : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
Class (IATA) : 2 - Gases

This document is only controlled at the time received electronically directly from Linde or while on the Linde Canada Inc. website where a copy of this controlled version is available for download. Linde cannot assure the integrity or accuracy of any version of this document after it has been electronically downloaded or removed from our website.





# NI - Pentane Mixture

## Safety Data Sheet E-7096

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06-01-2017

Revision date: 07-28-2023

Supersedes: 01-01-2021

Version: 1.1

### SECTION 15: Regulatory information

#### 15.1. National regulations

##### Nitrogen (7727-37-9)

Listed on the Canadian DSL (Domestic Substances List)

##### n-Pentane (109-66-0)

Listed on the Canadian DSL (Domestic Substances List)

#### 15.2. International regulations

##### Nitrogen (7727-37-9)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### n-Pentane (109-66-0)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Japanese ISHL (Industrial Safety and Health Law)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### SECTION 16: Other information

Date of issue : 01/06/2017

Revision date : 28/07/2023

Supersedes : 01/01/2021

Indication of changes:

Training advice : Ensure operators understand the flammability hazard.

Other information : When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Linde Canada asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Linde Canada Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Canada Inc, it is the user's obligation to determine the conditions of safe use of the product. Linde Canada Inc, SDSs are furnished on sale or delivery by Linde Canada Inc, or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Linde sales representative, local distributor, or supplier, or download from [www.lindecana.ca](http://www.lindecana.ca).





# NI - Pentane Mixture

## Safety Data Sheet E-7096

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 06-01-2017

Revision date: 07-28-2023

Supersedes: 01-01-2021

Version: 1.1

---

SDS Canada (GHS) - Linde NEW

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*